



Product Facts



Save energy and cost: i.e. 36W LED replaces a 72W fluorescent fitting, reducing the energy consumption by over 50% per unit.



Approved: SAA/C-tick (RCM).



Healthy: No IR or UV Radiation.



Call today: For a quote or a free energy assessment/payback plan: **1800 909 306** or email: sales@nedlandsgroup.com.au.



Where: Office, Healthcare, Retail, Recreation, Restaurant, Domestic and Commercial.



5 year warranty: Truly delivering your return on investment.

T36W-120/30
Ceiling Grid Install



T36W-60SQ



TV36W-120/30-NW



CLICK HERE TO:

ORDER

REQUEST FURTHER INFO

DOWNLOAD PHOTOMETRIC DATA



Key Benefits

- The POWER-LITE™ LED range has been developed over the past 6 years, working closely with the production team to bring an energy saving lighting solution within your reach.
- Low glare design provides a low impact lighting solution.
- With our global certification process, this product carries SAA/C-tick (RCM) certification, ensuring compliance.
- The POWER-LITE™ 5 year warranty is provided to ensure peace of mind and truly delivers your return on investment, whether utilising these units in new installations or retrofit projects.

Specifications & Dimensions

	T36W-60SQ-NW	T36W-60SQ-CW	T36W-120/30-NW	T36W-120/30-CW	TV36W-60SQ-NW	TV36W-120/30-NW
Power:	36W	36W	36W	36W	36W	36W
IP Rating:	IP20	IP20	IP20	IP20	IP20	IP20
Approvals:	SAA, C-tick (RCM)	SAA, C-tick (RCM)	SAA, C-tick (RCM)	SAA, C-tick (RCM)	SAA, C-tick (RCM)	SAA, C-tick (RCM)
Voltage:	AC 185-265V	AC 185-265V	AC 185-265V	AC 185-265V	AC 185-265V	AC 185-265V
Power Factor:	>0.9	>0.9	>0.9	>0.9	>0.9	>0.9
CRI:	>80	>80	>80	>80	>80	>80
UGR:	<19	<19	<19	<19	<19	<19
Material:	Steel & Aluminium	Steel & Aluminium	Steel & Aluminium	Steel & Aluminium	Steel & Aluminium	Steel & Aluminium
Lumen Output*:	3060 Lumens	3060 Lumens	3060 Lumens	3060 Lumens	3060 Lumens	3060 Lumens
Replaces*:	72W*	72W*	72W*	72W*	72W*	72W*
Beam Angle:	120°	120°	120°	120°	120°	120°
Size:	590 x 595 x 55mm	590 x 595 x 55mm	1195 x 295 x 55mm	1195 x 295 x 55mm	590 x 595 x 55mm	1195 x 295 x 55mm
LED Colour Temperature:	4000K	6000K	4000K	6000K	4000K	4000K
LED Driver:	Lifud® SAA / Non-Dimmable	Lifud® SAA / Non-Dimmable	Lifud® SAA / Non-Dimmable	Lifud® SAA / Non-Dimmable	Lifud® SAA / Non-Dimmable	Lifud® SAA / Non-Dimmable
LED Chip:	HONGLI 2835	HONGLI 2835	HONGLI 2835	HONGLI 2835	HONGLI 2835	HONGLI 2835
Warranty:	5 Years	5 Years	5 Years	5 Years	5 Years	5 Years
Life Span:	50,000 hours	50,000 hours	50,000 hours	50,000 hours	50,000 hours	50,000 hours
Operating Temp:	-30°C to 50°C	-30°C to 50°C	-30°C to 50°C	-30°C to 50°C	-30°C to 50°C	-30°C to 50°C
Frame Colour:	White / Chrome	White / Chrome	White / Chrome	White / Chrome	White / Chrome	White / Chrome
Nett Carton Weight:	2.5kg	2.5kg	2.5kg	2.5kg	2.5kg	2.5kg
Qty / Carton:	1	1	1	1	1	1
Connection:	1.2m Power Cable	1.2m Power Cable	1.2m Power Cable	1.2m Power Cable	1.2m Power Cable	1.2m Power Cable

*: The actual effects of the lumen output will depend on the application and environment, replacement wattage is approximate.

Notes and Next Action

CLICK HERE TO:

ORDER

REQUEST FURTHER INFO

DOWNLOAD PHOTOMETRIC DATA