

IES Indoor Report

Photometric Filename: B18W-CC-E-4K-2019-10-28.IES

Indoor Luminaire Photometric Data



Description Information

Lum. Name: B18W-CC-E	Lum. Catalog: LED BATTEN	Test ID:
Lamp Name: 4000K	Lamp Catalog: SMD2835	Test Date: 2019/10/28
Manufacture:	ShldAngle(°):	Test Machine: GON-2000
Test Lab:	Frequency(Hz):	Lamp CCT(K): Ra:
Lum. Size(W*L*H): 0.060m*0.600m*0.065m	Lum. Area(m2): 0.075	Lum. W(kg): 2.000
Test System: C, γ	Test Step: C=90.0 γ=5.0	Temp.(°C): 25
		Humidity(%):

Character Parameter

Lamp Speciality Parameter		Luminaire Speciality Parameter	
Rated Flux(lm): 1796.480	Luminaire Flux: 1796.475lm	Field Angle(10%Imax): 261.4	
Rated Power(W):	Luminaire Efficiency: 100.00%	Down Lumens&Percent: 1577.882lm 87.83%	
Rated Voltage(V):	Luminaire EER(lm/W): 95.966	Up Lumens&Percent: 218.594lm 12.17%	
Tested Power(W): 18.720	Max. Cand. (cd): 507.539	S/MH: C0_a180=1.309 C90_270=1.212	
Lamps' Inside: 1	Max Cand@Ang. (°): C=0.0 γ=0.0	CIE Type: General Diffuse	
Tested Electric: U=241.7V, I=0.084A, PF=0.000	Beam Angle(50%Imax): 129.1	ErP Φuse(120°): 1152.799lm	
Lamp Size(W*L*H): 0.060m*0.600m*0.065m	Left=-64.2 Right=64.9	IRF: 107.260%	

Lighting Distribution Diagram




IES Indoor Report

Photometric Filename: B18W-CC-E-4K-2019-10-28.IES

3D Light Intensity Distribution Modal

Lum. Name: B18W-CC-E	Lum. Catalog: LED BATTEN	Test ID:
Lamp Name: 4000K	Lamp Catalog: SMD2835	Test Lab:
Manufacture:	Test Machine: GON-2000	Test Date: 2019/10/28

3D Light Intensity Distribution Modal



Curves: 3D Model ——— Fixture ——— Vert. HUD ——— Hori. HUD ———
View Angles: Orient:0 Tilt:0 Roll:0 Spin:0

IES Indoor Report

Photometric Filename: B18W-CC-E-4K-2019-10-28.IES

Zonal Flux Tabulation


Zone (y)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp
0.0-5.0	12.11	12.11	0.67	0.67
5.0-10.0	35.91	48.02	2.00	2.67
10.0-15.0	58.52	106.54	3.26	5.93
15.0-20.0	79.13	185.67	4.40	10.34
20.0-25.0	97.02	282.69	5.40	15.74
25.0-30.0	111.64	394.33	6.21	21.95
30.0-35.0	122.63	516.96	6.83	28.78
35.0-40.0	129.76	646.72	7.22	36.00
40.0-45.0	132.93	779.65	7.40	43.40
45.0-50.0	132.16	911.81	7.36	50.76
50.0-55.0	127.59	1039.40	7.10	57.86
55.0-60.0	119.44	1158.84	6.65	64.51
60.0-65.0	108.02	1266.85	6.01	70.52
65.0-70.0	93.81	1360.66	5.22	75.74
70.0-75.0	77.53	1438.20	4.32	80.06
75.0-80.0	60.46	1498.65	3.37	83.42
80.0-85.0	44.87	1543.53	2.50	85.92
85.0-90.0	34.36	1577.88	1.91	87.83
90.0-95.0	29.81	1607.69	1.66	89.49
95.0-100.0	27.78	1635.47	1.55	91.04
100.0-105.0	25.84	1661.32	1.44	92.48
105.0-110.0	23.21	1684.52	1.29	93.77
110.0-115.0	20.11	1704.64	1.12	94.89
115.0-120.0	17.73	1722.36	0.99	95.87
120.0-125.0	15.59	1737.95	0.87	96.74
125.0-130.0	13.06	1751.01	0.73	97.47
130.0-135.0	10.74	1761.75	0.60	98.07
135.0-140.0	8.98	1770.73	0.50	98.57
140.0-145.0	7.46	1778.20	0.42	98.98
145.0-150.0	5.99	1784.19	0.33	99.32
150.0-155.0	4.51	1788.70	0.25	99.57
155.0-160.0	3.23	1791.93	0.18	99.75
160.0-165.0	2.24	1794.17	0.12	99.87
165.0-170.0	1.40	1795.57	0.08	99.95
170.0-175.0	0.71	1796.28	0.04	99.99
175.0-180.0	0.20	1796.48	0.01	100.00

IES Indoor Report

Photometric Filename: B18W-CC-E-4K-2019-10-28.IES

Rectangle ISO Lighting Intensity Diagram

Lum. Name: B18W-CC-E	Lum. Catalog: LED BATTEN	Test ID:
Lamp Name: 4000K	Lamp Catalog: SMD2835	Test Lab:
Manufacture:	Test Machine: GON-2000	Test Date: 2019/10/28




IES Indoor Report

Photometric Filename: B18W-CC-E-4K-2019-10-28.IES

Plane ISO-Illuminance Diagram

Lum. Name: B18W-CC-E	Lum. Catalog: LED BATTEN	Test ID:
Lamp Name: 4000K	Lamp Catalog: SMD2835	Test Lab:
Manufacture:	Test Machine: GON-2000	Test Date: 2019/10/28

Plane ISO-Illuminance Curve



Working Plane Luminaire Mounting Height(m): 3.00
 Working Plane Maximum Illuminance(lx): 56.39
 Working Plane Maximum Illuminance Position(d/h): H0.0 V0.0


IES Indoor Report

Photometric Filename: B18W-CC-E-4K-2019-10-28.IES

3D Plane ISO Illuminance Diagram

Lum. Name: B18W-CC-E	Lum. Catalog: LED BATTEN	Test ID:
Lamp Name: 4000K	Lamp Catalog: SMD2835	Test Lab:
Manufacture:	Test Machine: GON-2000	Test Date: 2019/10/28

3D Plane Illuminance Modal



Curves: 3D Model — 90% — 80% — 70% — 60% — 50% — 40% — 30% — 20% — 10% —
View Angles(deg): 0 Height(m): 3.0 Distance(m): 10.0


IES Indoor Report

Photometric Filename: B18W-CC-E-4K-2019-10-28.IES

Space ISO Illuminance Diagram

Lum. Name: B18W-CC-E	Lum. Catalog: LED BATTEN	Test ID:
Lamp Name: 4000K	Lamp Catalog: SMD2835	Test Lab:
Manufacture:	Test Machine: GON-2000	Test Date: 2019/10/28

Space ISO Illuminance Curve




Space Plane Maximum Illuminance and @Angle: 507.54, 0.0deg
Plane Maximum Lighting Intensity and @Angle: 507.539cd, 0deg

IES Indoor Report

Photometric Filename: B18W-CC-E-4K-2019-10-28.IES

Illuminance-Distance Diagram

Lum. Name: B18W-CC-E	Lum. Catalog: LED BATTEN	Test ID:
Lamp Name: 4000K	Lamp Catalog: SMD2835	Test Lab:
Manufacture:	Test Machine: GON-2000	Test Date: 2019/10/28



IES Indoor Report

Photometric Filename: B18W-CC-E-4K-2019-10-28.IES

Indoor Luminance Limiting Curves

Lum. Name: B18W-CC-E	Lum. Catalog: LED BATTEN	Test ID:
Lamp Name: 4000K	Lamp Catalog: SMD2835	Test Lab:
Manufacture:	Test Machine: GON-2000	Test Date: 2019/10/28


Glare Grade Table

GI	Quality	Using Illuminance							
		a	b	c	d	e	f	g	h
1.15	A	2000	1000	500	<=300				
1.5	B		2000	1000	500	<=300			
1.85	C			2000	1000	500	<=300		
2.2	D				2000	1000	500	<=300	
2.55	E	a				2000	1000	500	<=300
			b	c	d	e	f	g	h

Luminance Table

Gama (deg)	45	50	55	60	65	70	75	80	85
C0	7077	7197	7372	7621	7991	8578	9609	11861	19447
C90	5690	5475	5227	4925	4544	4036	3331	2322	975

Luminance Limiting Curve




Luminous Size: Length(m)=0.600 Width(m)=0.060 Height(m)=0.065 Area(m^2)=0.075000
 Luminous Type: Without Luminous Side
 Luminous Curves: C0-C180 Color: — C90-C270 Color: —

IES Indoor Report

Photometric Filename: B18W-CC-E-4K-2019-10-28.IES

Indoor Budgetary Estimate Table

Lum. Name: B18W-CC-E	Lum. Catalog: LED BATTEN	Test ID:
Lamp Name: 4000K	Lamp Catalog: SMD2835	Test Lab:
Manufacture:	Test Machine: GON-2000	Test Date: 2019/10/28



Parameters1: Rhocc = 0.7 Rhow = 0.5 Rhofc = 0.2 LLF = 0.8
 Parameters2: Rhocc = 0.5 Rhow = 0.3 Rhofc = 0.2 LLF = 0.8
 Average Illuminance(lx): 100 Cavity Height: H1(m) = 2

IES Indoor Report

Photometric Filename: B18W-CC-E-4K-2019-10-28.IES

Indoor Coefficient of Utilization Table

Lum. Name: B18W-CC-E	Lum. Catalog: LED BATTEN	Test ID:
Lamp Name: 4000K	Lamp Catalog: SMD2835	Test Lab:
Manufacture:	Test Machine: GON-2000	Test Date: 2019/10/28

Coefficients of Utilization - Zonal Cavity Method																		
Coef.	Effective Floor Cavity Reflectance RFC=0.20																	
RhoCC (%)	80				70				50			30			10			0
RhoW (%)	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR	Coefficient of Utilization (%)																	
0	116	116	116	116	112	112	112	112	104	104	104	97	97	97	91	91	91	88
1	105	99	95	90	101	96	92	88	89	86	83	83	81	78	78	76	74	71
2	95	86	79	73	91	83	76	71	77	72	67	72	68	64	68	64	61	58
3	86	75	67	60	82	73	65	58	68	61	56	63	58	53	59	55	51	48
4	79	66	57	50	75	64	56	49	60	53	47	56	50	45	53	48	43	41
5	72	59	50	43	69	57	49	42	54	46	41	50	44	39	47	42	38	35
6	66	53	44	37	64	51	43	37	48	41	35	45	39	34	43	37	33	31
7	62	48	39	33	59	47	38	32	44	37	31	41	35	30	39	33	29	27
8	57	44	35	29	55	42	34	29	40	33	28	38	32	27	36	30	26	24
9	53	40	32	26	51	39	31	26	37	30	25	35	29	24	33	28	23	22
10	50	37	29	24	48	36	28	23	34	27	23	32	26	22	31	25	21	19

IES Indoor Report

Photometric Filename: B18W-CC-E-4K-2019-10-28.IES

Unified Glare Rating Table

Lum. Name: B18W-CC-E	Lum. Catalog: LED BATTEN	Test ID:
Lamp Name: 4000K	Lamp Catalog: SMD2835	Test Lab:
Manufacture:	Test Machine: GON-2000	Test Date: 2019/10/28

Unified Glare Rating Table

Ceiling RCC	0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
Wall RW	0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
Floor RFC	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
Room Size	Viewed crosswise					Viewed endwise				
X=2H Y=2H	23.7	26.9	24.9	28.2	29.5	21.6	24.8	22.8	26.1	27.4
Y=3H	29.8	33.1	31.0	34.4	35.7	25.6	28.9	26.8	30.2	31.5
Y=4H	33.7	36.6	35.0	37.9	39.2	27.8	30.7	29.1	32.0	33.4
Y=6H	37.3	40.1	38.6	41.4	42.8	29.0	31.8	30.3	33.1	34.4
Y=8H	39.2	42.0	40.6	43.3	44.7	29.3	32.1	30.6	33.4	34.7
Y=12H	41.4	44.2	42.7	45.5	46.9	29.4	32.2	30.7	33.5	34.9
X=4H Y=2H	24.8	27.7	26.1	29.0	30.3	24.0	26.9	25.3	28.2	29.5
Y=3H	31.2	34.1	32.5	35.4	36.8	28.4	31.3	29.7	32.6	33.9
Y=4H	33.6	35.4	35.2	37.0	38.6	29.2	31.0	30.8	32.6	34.2
Y=6H	37.9	39.5	39.5	41.1	42.7	31.0	32.7	32.7	34.3	35.9
Y=8H	40.2	41.8	41.8	43.4	45.0	31.7	33.3	33.3	34.9	36.5
Y=12H	42.0	43.4	43.8	45.1	46.8	31.2	32.6	32.9	34.3	36.0
X=8H Y=4H	33.9	35.5	35.5	37.1	38.7	30.5	32.1	32.1	33.6	35.2
Y=6H	37.6	38.8	39.4	40.5	42.2	32.0	33.2	33.8	34.9	36.6
Y=8H	39.8	40.7	41.6	42.5	44.3	32.7	33.6	34.5	35.4	37.1
Y=12H	43.0	43.9	44.8	45.7	47.4	33.6	34.5	35.4	36.3	38.0
X=12H Y=4H	33.0	34.4	34.8	36.1	37.8	29.9	31.2	31.6	32.9	34.6
Y=6H	37.2	38.1	39.0	39.9	41.7	32.1	33.0	33.9	34.8	36.6
Y=8H	39.9	40.8	41.7	42.6	44.3	33.4	34.3	35.3	36.1	37.8
Variations with the observer position at spacings										
S=1.0H	2.0/-2.2					2.3/-0.1				
S=1.5H	-2.2/-20.7					-0.1/-16.3				
S=2.0H	-2.2/-20.7					-0.1/-16.3				

IES Indoor Report

Photometric Filename: B18W-CC-E-4K-2019-10-28.IES

Candela Tabulation

V/H	C0.0	C90.0	C180.0	C270.0
Y 0.0	507.54	507.54	507.54	507.54
Y 5.0	506.30	502.35	506.03	505.86
Y 10.0	502.26	492.12	501.52	499.15
Y 15.0	494.44	476.55	493.27	486.89
Y 20.0	482.59	456.23	480.91	469.54
Y 25.0	466.89	431.61	464.83	447.52
Y 30.0	447.79	403.25	445.41	421.51
Y 35.0	425.80	371.90	423.26	392.06
Y 40.0	401.66	337.86	398.73	359.64
Y 45.0	375.29	301.74	372.04	324.79
Y 50.0	346.97	263.94	343.45	288.00
Y 55.0	317.13	224.84	313.28	249.62
Y 60.0	285.80	184.67	281.46	210.07
Y 65.0	253.29	144.03	248.37	169.60
Y 70.0	220.03	103.53	214.34	128.73
Y 75.0	186.53	64.66	180.27	88.41
Y 80.0	154.48	30.25	148.56	50.62
Y 85.0	127.12	6.37	123.54	19.66
Y 90.0	110.57	1.21	109.33	4.11
Y 95.0	103.11	1.37	102.62	3.19
Y 100.0	96.89	1.78	97.02	2.99
Y 105.0	91.32	2.17	91.20	2.97
Y 110.0	79.38	2.59	82.15	3.34
Y 115.0	72.84	3.06	70.77	3.61
Y 120.0	67.41	3.52	66.49	3.97
Y 125.0	60.53	3.94	59.69	4.21
Y 130.0	50.80	4.31	52.24	4.52
Y 135.0	44.50	4.76	46.81	4.74
Y 140.0	41.02	5.12	41.91	5.13
Y 145.0	37.62	5.46	37.27	5.44
Y 150.0	32.80	5.79	32.61	5.83
Y 155.0	27.01	6.07	26.36	6.13
Y 160.0	22.60	6.45	22.21	6.49
Y 165.0	18.85	6.76	18.41	6.76
Y 170.0	14.97	7.04	14.44	7.10
Y 175.0	11.37	7.18	10.07	7.29
Y 180.0	7.37	7.37	7.37	7.37
