



LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:240.5V I:0.0540A P:12.40W PF:0.9620 Lamp Flux:1287.46x1 lm		
NAME: LED-DL13WCOB-5K-W	TYPE:13W	WEIGHT:
DIM.:	SPEC.:5000K	SERIAL No.:1
MFR.:	SUR.:0.04	PROTECTION ANGLE:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 103.83 lm/W			
MODEL	LED-DL13WCOB-5K-W	I _{max} (cd)	1410	S/MH(C0/180)	0.80
NOMINAL POWER(W)	13	LOR(%)	100.0	S/MH(C90/270)	0.82
RATED VOLTAGE(V)	240	TOTAL FLUX(lm)	1287.5	η UP, DN(C0-180)	0.0, 49.8
NOMINAL FLUX(lm)	1287.46	CIE CLASS	DIRECT	η UP, DN(C180-360)	0.0, 50.2
LAMPS INSIDE	1	η up(%)	0.0	CIBSE SHR NOM	1.00
TEST VOLTAGE(V)	240.5	η down(%)	100.0	CIBSE SHR MAX	1.00



C Range: 0 - 360DEG
 C Interval: 30.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:DAMIN
 Test Date:2018-04-11

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.276
 Humidity:65.0%
 Test Distance:9.600m [K=1.0000]
 Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	Φ lum,lamp
10	1280	1289	1285	1274	1271	1274	1272	1267	0- 10	128.7	128.7	9.99,9.99
20	934.2	950.7	949.8	936.4	932.0	936.9	935.4	924.4	10- 20	307.7	436.4	33.9,33.9
30	650.1	659.1	665.5	666.6	671.0	675.1	669.3	652.4	20- 30	367.8	804.2	62.5,62.5
40	392.7	384.4	381.1	406.0	410.5	408.1	408.9	394.6	30- 40	322.6	1127	87.5,87.5
50	24.10	23.81	24.91	25.61	29.50	30.84	26.09	24.10	40- 50	114.6	1241	96.4,96.4
60	17.42	17.73	17.89	18.31	18.90	18.38	17.72	17.09	50- 60	18.40	1260	97.9,97.9
70	14.00	14.07	14.18	14.39	15.38	15.98	15.12	13.73	60- 70	16.77	1277	99.2,99.2
80	4.397	4.604	3.917	2.225	1.951	2.139	2.344	2.718	70- 80	10.38	1287	100,100
90	0	0	0	0	0	0	0	0	80- 90	0.4473	1287	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		


C Range: 0 - 360DEG
 C Interval: 30.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:DAMIN
 Test Date:2018-04-11

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.276
 Humidity:65.0%
 Test Distance:9.600m [K=1.0000]
 Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:240.5V I:0.0540A P:12.40W PF:0.9620 Lamp Flux:1287.46x1 lm		
NAME: LED-DL13WCOB-5K-W	TYPE:13W	WEIGHT:
DIM.:	SPEC.:5000K	SERIAL No.:1
MFR.:	SUR.:0.04	PROTECTION ANGLE:

pcc	80%			70%			50%			30%			10%			0
	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pw																
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio															
	Coefficients of Utilization(CU)															
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	.00
1.0	1.10	1.07	1.05	1.08	1.06	1.03	1.04	1.02	1.00	1.00	.99	.97	.97	.95	.94	.93
2.0	1.02	.97	.94	1.00	.96	.93	.97	.94	.91	.94	.91	.89	.91	.89	.87	.85
3.0	.94	.89	.85	.93	.88	.84	.90	.86	.83	.88	.84	.81	.85	.83	.80	.78
4.0	.88	.82	.77	.86	.81	.77	.84	.79	.76	.82	.78	.75	.80	.77	.74	.72
5.0	.82	.75	.71	.81	.75	.70	.79	.74	.70	.77	.73	.69	.75	.72	.69	.67
6.0	.76	.70	.65	.75	.69	.65	.74	.68	.65	.72	.68	.64	.71	.67	.64	.62
7.0	.71	.65	.60	.71	.65	.60	.69	.64	.60	.68	.63	.60	.67	.63	.59	.58
8.0	.67	.60	.56	.66	.60	.56	.65	.60	.56	.64	.59	.56	.63	.59	.55	.54
9.0	.63	.57	.52	.62	.56	.52	.61	.56	.52	.60	.55	.52	.60	.55	.52	.50
10.0	.59	.53	.49	.59	.53	.49	.58	.53	.49	.57	.52	.49	.56	.52	.49	.47



C Range: 0 - 360DEG
 C Interval: 30.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: DAMIN
 Test Date: 2018-04-11

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.276
 Humidity: 65.0%
 Test Distance: 9.600m [K=1.0000]
 Remarks:

WEC AND CCEC

Test:U:240.5V I:0.0540A P:12.40W PF:0.9620 Lamp Flux:1287.46x1 lm		
NAME: LED-DL13WCOB-5K-W	TYPE:13W	WEIGHT:
DIM.:	SPEC.:5000K	SERIAL No.:1
MFR.:	SUR.:0.04	PROTECTION ANGLE:

ρcc	80%			70%			50%			30%			10%			0
ρw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)									
0.0																
1.0	.190	.108	.034	.184	.105	.033	.171	.098	.031	.159	.092	.029	.149	.086	.028	
2.0	.183	.100	.031	.177	.098	.030	.167	.093	.029	.157	.088	.028	.148	.084	.026	
3.0	.174	.093	.028	.170	.091	.027	.160	.087	.026	.152	.083	.026	.144	.080	.025	
4.0	.166	.086	.025	.162	.085	.025	.154	.082	.024	.146	.079	.024	.139	.076	.023	
5.0	.158	.080	.023	.154	.079	.023	.147	.077	.023	.141	.074	.022	.135	.072	.022	
6.0	.150	.075	.022	.147	.074	.021	.141	.072	.021	.135	.070	.021	.130	.068	.020	
7.0	.143	.071	.020	.141	.070	.020	.135	.068	.020	.130	.067	.019	.125	.065	.019	
8.0	.137	.067	.019	.134	.066	.019	.130	.065	.018	.125	.063	.018	.121	.062	.018	
9.0	.131	.063	.018	.129	.063	.018	.124	.061	.017	.120	.060	.017	.116	.059	.017	
10.0	.125	.060	.017	.123	.060	.017	.119	.058	.016	.116	.057	.016	.112	.056	.016	

ρcc	80%			70%			50%			30%			10%			0
ρw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.172	.157	.144	.147	.135	.124	.101	.093	.086	.058	.054	.050	.019	.017	.016	
2.0	.158	.132	.111	.135	.114	.096	.093	.079	.067	.053	.046	.039	.017	.015	.013	
3.0	.146	.114	.088	.125	.098	.076	.086	.068	.053	.050	.040	.031	.016	.013	.010	
4.0	.136	.099	.071	.117	.086	.061	.080	.060	.043	.047	.035	.026	.015	.011	.008	
5.0	.128	.088	.058	.110	.076	.050	.076	.053	.036	.044	.031	.021	.014	.010	.007	
6.0	.121	.079	.048	.104	.068	.042	.072	.048	.030	.042	.028	.018	.013	.009	.006	
7.0	.115	.071	.041	.098	.062	.036	.068	.043	.025	.040	.025	.015	.013	.008	.005	
8.0	.109	.065	.035	.094	.056	.030	.065	.040	.022	.038	.023	.013	.012	.008	.004	
9.0	.104	.060	.030	.089	.052	.026	.062	.037	.019	.036	.022	.011	.012	.007	.004	
10.0	.099	.056	.027	.086	.048	.023	.059	.034	.016	.035	.020	.010	.011	.007	.003	

C Range: 0 - 360DEG
 C Interval: 30.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:DAMIN
 Test Date:2018-04-11

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.276
 Humidity:65.0%
 Test Distance:9.600m [K=1.0000]
 Remarks:

Uncorrected UGR Table

Test:U:240.5V I:0.0540A P:12.40W PF:0.9620 Lamp Flux:1287.46x1 lm										
NAME: LED-DL13WCOB-5K-W					TYPE:13W			WEIGHT:		
DIM.:					SPEC.:5000K			SERIAL No.:1		
MFR.:					SUR.:0.04			PROTECTION ANGLE:		
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	21.5	22.6	21.8	22.7	22.9	21.6	22.6	21.8	22.8	22.9
3H	21.5	22.5	21.8	22.7	22.9	21.6	22.5	21.8	22.7	22.9
4H	21.6	22.5	21.9	22.7	22.9	21.6	22.5	21.9	22.7	23.0
6H	21.6	22.4	21.9	22.6	22.9	21.6	22.4	21.9	22.7	22.9
8H	21.5	22.3	21.8	22.6	22.8	21.6	22.4	21.9	22.6	22.9
12H	21.5	22.2	21.8	22.5	22.8	21.5	22.3	21.8	22.6	22.8
4H 2H	21.3	22.2	21.6	22.5	22.7	21.4	22.3	21.7	22.5	22.7
3H	21.4	22.2	21.8	22.5	22.8	21.5	22.2	21.8	22.5	22.8
4H	21.5	22.2	21.9	22.5	22.8	21.6	22.3	21.9	22.6	22.9
6H	21.6	22.2	21.9	22.5	22.8	21.6	22.2	22.0	22.5	22.9
8H	21.5	22.1	21.9	22.4	22.8	21.6	22.1	22.0	22.5	22.8
12H	21.5	22.0	21.9	22.4	22.7	21.5	22.0	21.9	22.4	22.8
8H 4H	21.5	22.0	21.9	22.4	22.8	21.5	22.1	21.9	22.4	22.8
6H	21.5	22.0	22.0	22.4	22.8	21.6	22.0	22.0	22.4	22.8
8H	21.5	21.9	21.9	22.3	22.8	21.5	21.9	22.0	22.4	22.8
12H	21.4	21.8	21.9	22.2	22.7	21.5	21.8	21.9	22.3	22.7
12H 4H	21.4	21.9	21.8	22.3	22.7	21.5	22.0	21.9	22.4	22.8
6H	21.5	21.9	21.9	22.3	22.8	21.5	21.9	22.0	22.4	22.8
8H	21.5	21.8	21.9	22.2	22.7	21.5	21.8	22.0	22.3	22.8
Variations with the observer position at spacings:										
S = 1.0H	+ 2.5 / - 5.8					+ 2.5 / - 5.7				
1.5H	+ 4.9 / - 5.8					+ 5.0 / - 5.7				
2.0H	+ 3.6 / - 0.8					+ 3.7 / - 0.8				

CIE Pub.117 Corrected 1287 lm Total Lamp Luminous Flux.(8log(F/F0) = 0.9)

C Range: 0 - 360DEG
 C Interval: 30.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:DAMIN
 Test Date:2018-04-11

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.276
 Humidity:65.0%
 Test Distance:9.600m [K=1.0000]
 Remarks:

UTILIZATION FACTORS TABLE

Test:U:240.5V I:0.0540A P:12.40W PF:0.9620 Lamp Flux:1287.46x1 lm		
NAME: LED-DL13WCOB-5K-W	TYPE:13W	WEIGHT:
DIM.:	SPEC.:5000K	SERIAL No.:1
MFR.:	SUR.:0.04	PROTECTION ANGLE:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	84	77	73	83	77	73	82	76	72	69
0.80	92	85	81	91	85	81	90	84	81	77
1.00	97	91	87	96	90	86	94	90	86	82
1.25	101	95	92	100	95	91	98	94	90	86
1.50	104	99	95	103	98	95	101	97	94	89
2.00	107	103	99	106	102	99	103	100	97	92
2.50	109	105	102	108	104	101	104	101	99	93
3.00	111	107	104	109	106	103	106	103	101	94
4.00	113	110	108	111	108	106	107	105	104	96
5.00	114	112	110	112	110	108	108	107	105	97
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended				SHRNOM = 1.25			

C Range: 0 - 360DEG
 C Interval: 30.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:DAMIN
 Test Date:2018-04-11

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.276
 Humidity:65.0%
 Test Distance:9.600m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:240.5V I:0.0540A P:12.40W PF:0.9620 Lamp Flux:1287.46x1 lm		
NAME: LED-DL13WCOB-5K-W	TYPE:13W	WEIGHT:
DIM.:	SPEC.:5000K	SERIAL No.:1
MFR.:	SUR.:0.04	PROTECTION ANGLE:




C Range: 0 - 360DEG
C Interval: 30.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2018-04-11

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.276
Humidity:65.0%
Test Distance:9.600m [K=1.0000]
Remarks:

AAI Figure

Test:U:240.5V I:0.0540A P:12.40W PF:0.9620 Lamp Flux:1287.46x1 lm		
NAME: LED-DL13WCOB-5K-W	TYPE:13W	WEIGHT:
DIM.:	SPEC.:5000K	SERIAL No.:1
MFR.:	SUR.:0.04	PROTECTION ANGLE:




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 30.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:DAMIN
 Test Date:2018-04-11

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.276
 Humidity:65.0%
 Test Distance:9.600m [K=1.0000]
 Remarks:

ISOLUX DIAGRAM


Test:U:240.5V I:0.0540A P:12.40W PF:0.9620 Lamp Flux:1287.46x1 lm		
NAME: LED-DL13WCOB-5K-W	TYPE:13W	WEIGHT:
DIM.:	SPEC.:5000K	SERIAL No.:1
MFR.:	SUR.:0.04	PROTECTION ANGLE:



C Range: 0 - 360DEG
 C Interval: 30.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:DAMIN
 Test Date:2018-04-11

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.276
 Humidity:65.0%
 Test Distance:9.600m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
 C Interval: 30.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: DAMIN
 Test Date: 2018-04-11

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.276
 Humidity: 65.0%
 Test Distance: 9.600m [K=1.0000]
 Remarks:

