LED Recessed Grid Luminaire

User Manual Instruction

Please read these instructions carefully before commencing installation. Please keep the instructions for future reference.

The scope of application:

Hotel, meeting room, factory or office, residential and public facilities, commercial, schools, hospitals etc.

SAFETY HINT:

- 1. If you have any doubt, consult a qualified electrical.
- 2. Suitable for indoor use only, this product must be connected to Earth.
- 3. Disconnect the main power before installation.
- 4. This product is only suitable for use in dry areas (not for constant moisture area), not recommended for use in bathrooms;
- 5. The chosen location of your new fitting should allow for the product to be securely mounted (e.g. to a ceiling joist) and safely connected to the mains supply (lighting circuit).
- 6. If the location of your new fitting requires the provision of a new electrical supply, the supply must conform to the requirements of the latest edition of the IEEE wiring regulations.
- 7. The luminaire must not under any circumstance be covered with heat insulating covers or similar materials.

TECHNICAL SPECIFICATION:

Model type	Rated voltage,	Power	Protection	IP	Та	Product	Installation
	frequency		Class	degree		Dimension	Dimension
	-			18		(LxWxH)	(LxW)
T36W-60SQ-NW	220-240V/50/60Hz	36W	Class I	IP20	40°C	595mm×595m	580mm×580mm
						mx55mm	
T36W-60SQ-CW	220-240V/50/60Hz	36W	Class I	IP20	40°C	595mm×595m	580mm×580mm
						mx55mm	
T36W-120/30-NW	220-240V/50/60Hz	36W	Class I	IP20	40°C	1195mm×295	1180mm×280m
			11			mmx55mm	m
T36W-120/30-CW	220-240V/50/60Hz	36W	Class I	IP20	40°C	1195mm×295	1180mm×280m
						mmx55mm	m
TV36W-120/30-NW	220-240V/50/60Hz	36W	Class I	IP20	40°C	1195mm×295	1180mm×280m
			P.,			mmx85mm	m

Page 1 of 3





T36W-60SQ-NW T36W-60SQ-CW





INSTALLATION

