

DIMMER SWITCH—PUSH/ ROTARY

Applications:

Used on all residential and commercial lighting installations.



Specifications

Approvals:	SAA/C-tick (RCM), AS/NZS 3100, AS/NZS 3133, IEC 60669-2-1
Control Method:	One way or Two way
Dimmable LED Lamps <i>(Dimmer Push Switch Function Disabled)</i>	5-250W (Load Min/ Max)
Incandescent Halogen <i>(Dimmer Push Switch Function Disabled)</i>	10-400W (Load Min/ Max)
Dimmable LED Lamps <i>(Dimmer Push Switch Function Enabled)</i>	16-250W (Load Min/ Max)
Incandescent Halogen <i>(Dimmer Push Switch Function Enabled)</i>	16-400W (Load Min/ Max)
Working Temperature:	-20°C to +80°C
Humidity:	<75%
Over Temperature Protection:	Manual Rest
Compatible Loads:	Power-Lite LED Luminaires*
Dimming Range:	3% to 100% (Load dependent)
Warranty:	5 Years
Colour:	White
Carton Quantity:	20



Note: Face plate and switch not included. Fits HPM & Clipsal Wall Plates.

*Due to the vast range of LED luminaires currently on the market, POWER-LITE is unable to take liability or responsibility for any incompatibility or warranty issues arising from the use of POWER-LITE dimmers with non-POWER-LITE products.

Code	Type of Dimmer	Voltage	Dimming Operation
DS-RP	Rotary Dimmer Switch with Push Button on/off	AC220-240V—50Hz	Trailing Edge