



LED DOWNLIGHTS

The POWER-LITE® LED Downlights save energy and cost as compared to standard halogen downlights. These come with a built-in LED driver with IC-4 insulation rating for easy install.

Applications:

Commercial, Industrial & Domestic.



Specifications

| | |
|----------------------|----------------------------------|
| LED Chip: | Epistar SMD |
| Beam Angle: | 90° |
| IP Rating: | IP44 |
| Frame Colour: | White |
| LED Driver: | Dimmable |
| Warranty: | 3 Years |
| CRI: | 80 |
| Connection: | 0.6m Power Cable with an AU Plug |
| LED Driver: | Dimmable |
| Voltage: | 200-240V AC |

Note: This downlight range is compatible with C-BUS / Trailing edge dimming systems. It is recommended to test it, before carrying out a large installation as some C-BUS systems may not be compatible.



ID13W-CC



ID20W-CC



ID33W-CC



| Code | Power | Colour Temperature | Lumen Output | Dimensions | Cut Out Size | Carton Qty |
|----------|-------|-----------------------|------------------|---------------|--------------|------------|
| ID13W-CC | 13W | 3000K, 4000K or 5700K | 1110-1355 Lumens | Ø152mm x 48mm | 125mm-140mm | 24 |
| ID20W-CC | 20W | 3000K, 4000K or 5700K | 1710-2090 Lumens | Ø175mm x 52mm | 145mm-160mm | 12 |
| ID33W-CC | 33W | 3000K, 4000K or 5700K | 2820-3445 Lumens | Ø228mm x 63mm | 205mm-215mm | 6 |