

## LED INTEGRAL DRIVER DOWNLIGHT

The POWER-LITE® LED Integral Downlight saves energy and costs as compared to standard halogen downlights. These come with a built-in LED driver with IC-4 insulation rating for easy install. This downlight includes the elimination of UV therefore insects will not be attracted to this light.

### Applications:

Domestic, Commercial & Retail.

### Specifications

<b>Power:</b>	8W
<b>LED Chip:</b>	Epistar 2835
<b>Colour Temperature:</b>	Colour Changing (3000K-4000K -5700K)
<b>Warranty:</b>	5 Years
<b>Life Expectancy:</b>	40,000 Hours
<b>Working Temperature:</b>	-20°C to +45°C
<b>CRI:</b>	>80
<b>Beam Angle:</b>	90°
<b>Approvals:</b>	SAA/C-tick (RCM)
<b>Voltage:</b>	AC200-240V
<b>IP Rating:</b>	IP54
<b>LED Driver:</b>	Dimmable/Integral/IC-4
<b>Connection:</b>	1.2m Lead & Plug
<b>Frame Colour:</b>	White
<b>Carton Quantity:</b>	30



ID8W-CC



Hard wired installation option



ID-BC



ID-BLACK



ID10W-RF-140

### NOTES:

Compatible with Clipsal C-Bus dimming system

Note: IC-F / IC-4 rated downlights, can be covered and abutted with building materials which can be safely exposed to temperatures of up to 90°C.

Code	Frame Colour	Description	Dimensions	Cut out	Lumen Output
ID8W-CC	White	Downlight	Ø115 x 61mm	90-95mm	765-870LM
ID-BC	Brushed Chrome	Ring for Downlight	-	-	-
ID-BLACK	Black	Ring for Downlight	-	-	-
ID10W-RF-140	White	140mm Retrofit Ring	-	-	-