

LED ECO HIGHBAY LIGHT 100W

The POWER-LITE® LED High Bay provides an instant start up with no warm up process and up to 75% energy saving.







Applications:

Warehouse, Factory & Sports halls.

Specifications				
Power:	100W			
Voltage:	AC90-305V			
Start Up Current:	1.2A			
Colour Temperature:	6000K			
Warranty:	5 Years			
Life Expectancy:	50,000 Hours (LM70)			
Working Temperature:	-30°C to +50°C			
Power Factor:	>0.95			
Beam Angle:	110°			
Approvals:	SAA/C-tick (RCM)			
IP Rating:	IP66			
CRI:	80			
Maintenance Factor:	>79%			
Lumen Output:	13,500			
Nett Weight:	2.6kg			
Aluminium Housing:	Black Body & Black Trim			
Lens Type:	Clear PC			
IK Rating:	IK10			
Replaces:	400 W Metal Halide			
Connections:	1.5m Power cable with SAA plug			









UFO-E-PCM

UFO-E-S

Code	Description	Wattage	Carton Quantity	Dimensions
UFO-100W-E		100W	4	Ø390 x 154.6mm
UFO-E-S	Motion Sensor	-	1	-
UFO-E-PCM	Milky PC Lens	-	1	-
UFO-150W-E-PRISMATIC	Prismatic Diffuser for UFO-100W-E			



Free Call: 1800 909 306

Website: nedlandsgroup.com.au

Sales: sales@nedlandsgroup.com.au