

LED Strip Light

The POWER-LITE® LED Strip Light not only provides a lifelong lighting solution, saving in energy and maintenance costs, but provides a very even light distribution.

Applications:

Commercial, Retail and Residential



Specifications


Approvals:	SAA / C-TICK (RCM)
Beam Angle:	120°
Life Span:	40,000 hours
Operating Temperature:	-20°C-60°C
Power Factor:	>0.9
CRI:	90
LED Chip:	2835
Carton Quantity:	1
LED's/m:	240



FLS86W-D



FLS-D-200W & FLS-D-250W



FLS86W-D-PL-AL055

Note: The IP67 Rating LED Strip Light cannot be cut and joined.

Code	Power	LED Driver	Warranty	Colour Temp	Voltage	IP Rating	Lumen Output / m	Dimensions
FLS100W-NW-IP67	100W (20W/m)	Supplied Separately	3 Years	4000K	DC24V	IP67	2800 LM/m	10mm (W) x 5m(L)
FLS100W-WW-IP67	100W (20W/m)	Supplied Separately	3 Years	3000K	DC24V	IP67	2800 LM/m	10mm (W) x 5m(L)
FLS200W-NW-IP67	200W (20W/m)	Supplied Separately	3 Years	4000K	DC24V	IP67	2800 LM/m	10mm (W) x 10m(L)
FLS200W-WW-IP67	200W (20W/m)	Supplied Separately	3 Years	3000K	DC24V	IP67	2800 LM/m	10mm (W) x 10m(L)
FLS86W-D	-	100W SAA Driver—0—10V Dimmable	-	-	AC100-240V	IP20	-	-
FLS86W-D-PL-AL055	-	0-10V Dimmable	-	-	DC24V	IP67	-	-
FLS-D-200W	-	200W DRIVER — 0-10V Dimmable	5 Years	-	DC24V	IP67	-	-
FLS-D-250W	-	250W Driver — 0-10V Dimmable	5 Years	-	DC24V	IP67	-	-