

PL-AT3016

12W LED Oval and Round bunker - Supplied with Eyelid

option

Features

- 12W LED Polycarbonate bunker - IP66 with eyelid option included.
- Insect Resistant seal
- Eyelid option included
- Ideal for Residential, commercial, and decorative



Mechanical

Adjustability	Fixed
Body Material	Polycarbonate
Diffuser Material	Polycarbonate
Product Finish	Plastic
Fitting Colour	Black

IC Rating	Non-IC
IK Rating	IK8
Installation Type	Surface mount
IP Rating	IP66

Electrical

Electrical Rating (Class)	2
Input Frequency (Hz)	50
Input voltage	230Vac
In Australia the Input voltage is defined as 230Vac -6%/+10%. This effectively means that the voltage range of these products are 216Vac - 253Vac or 240V +6%	
Maximum Wattage (w)	12
Switch Type	Inline
Working Temp Range (C)	-20 to 45

Lamp

Beam Angle (Deg)	120
CCT Configuration	Single
CRI	>80
LED Type	Diffused
Number of Lamps	1

Colour temperature

AT3016/BLK/OH/CW

12 Watts

Cool White (4000)	955 lm
Cool White (4000-Eyelid)	520 lm

AT3016/BLK/RD/CW

12 Watts

Cool White (4000K)	1010 lm
Cool White (4000K -eyelid)	520 lm

AT3016/WH/OH/CW

Cool White (4000)	920 lm
-------------------	--------

12 Watts

Cool White (4000-eyelid)	600 lm
--------------------------	--------

AT3016/WH/RD/CW

12 Watts	
Cool White (4000K)	1050 lm
Cool White (4000K-eyelid)	665 lm

Driver

Dimmable	No
Driver Included	Yes
Integrated Driver	Yes
Driver Mode	Constant Current
Driver Type	Fixed output
Wiring Type	Re-wireable terminal block (3 pin)

Energy Savings Scheme

Ipart Approval	Yes
REES Approval	Yes
VEU Approval	Yes

Compliance

Standards	AS/NZS 60598.1 AS/NZS 60598.2.1 AS/NZS 61347.1 AS/NZS 61347.2.13 AS/NZS CISPR 15
------------------	--

Warranty

Commercial Use Warranty	3 (Yr) RTB
Domestic Use Warranty	3 (Yr) RTB

Dimensions


Product Diameter(mm)	300
Product Height (mm)	90
Product Length (mm)	
AT3016/BLK/OH/CW AT3016/WH/OH/CW	330
AT3016/BLK/RD/CW AT3016/WH/RD/CW	300
Product Width (mm)	
AT3016/BLK/OH/CW AT3016/WH/OH/CW	230
AT3016/BLK/RD/CW AT3016/WH/RD/CW	300

Ordering Information


Order code	Item Code	Description
11132	AT3016/BLK/OH/CW	Oval 12W LED Polycarbonate Bunker - IP66 w/Eyelid option - Black colour - CW
11179	AT3016/BLK/RD/CW	Round 12W LED Polycarbonate Bunker - IP66 w/Eyelid option - Black Colour - CW
11188	AT3016/WH/OH/CW	Oval 12W LED Polycarbonate Bunker - IP66 w/Eyelid option - White Colour - CW
11171	AT3016/WH/RD/CW	Round 12W LED Polycarbonate Bunker - IP66 w/Eyelid option - White Colour - CW

Photometrics


AT3016/WH/RD/CW



AT3016/WH/RD/CW/EYELID



AT3016/WH/OH/CW/EYELID



AT3016/WH/OH/CW

