



## LED CYANOSIS



CDL12W, CDL40W

The POWER-LITE® LED Cyanosis Downlight is designed to meet the required COI for specific medical environments.





1800 909 306 nedlandsgroup.com.au sales@nedlandsgroup.com.au







APPLICATIONS Commercial

Medical | Retail Industrial



## DIMENSIONS

## (mm)


## Note:

\_

CDL12W-NW Cutout Diameter Height

90-95 115 55






CDL40W-NW Cutout Diameter Height

Φ252

PRODUCT





**SPECIFICATIONS** 

LED Chip 2835 SMD

Life Expectancy 50,000 hrs TM-21

Working Temp -20°C to +65°C

CRI >90

> COI <3

Efficacy Up to 102lm/W

IP65 for downlight only (driver is IP20 rated)

LED Driver Triac Dimmable Flicker Free

Connection 1.2m White Cable with AU Plug



IP65

120°

Beam Angle

IP


TRODUCT	of Eon IoAnono		CODE
LED CYANOSIS DOWNLIGHT	<b>12W</b> <b>Carton Qty</b> 27	<b>4000K</b> 900lm	CDL12W-NW
	40W Carton Qty 10	<b>4000K</b> 3400lm	CDL40W-NW








PHOTOMETRICS









1800 909 306 nedlandsgroup.com.au sales@nedlandsgroup.com.au