













13W LED COB

DOWNLIGHT

LED-DL13WCOB

The POWER-LITE® 13W LED COB Downlight is the ideal replacement for traditional halogen downlights. The narrow beam angle with COB LED Chip provides a focused light with great aesthetics. This downlight includes the elimination of UV therefore insects will not be attracted to this light.

APPLICATIONS

Domestic

Retail

Commercial

Healthcare





1800 909 306



nedlandsgroup.com.au



sales@nedlandsgroup.com.au




Certainty at The Speed of Light


DIMENSIONS (mm) Cutout 90

Diameter 110 Height 53

Note

IC-4 rated for downlight only (driver is NOT IC-4 rated)





LED Chip Power Factor Epistar COB ≥0.9

Life Expectancy Efficacy

50,000 hrs TM-21 Up to 103lm/W

Working Temp
-20°C to +45°C

LED Driver
Dimmable

CRI Connection
≥80 LED Driver, 60

LED Driver, 600mm Lead & Plug

& Flug

Carton Qty

30

\ \\\	
F	

AC100-240V

PRODUCT	OPTIONS		CODE
13W LED COB DOWNLIGHT	3000K 800lm	Black	LED-DL13WCOB-WW-B
		White	LED-DL13WCOB-WW-W
	4000K 1140lm	Black	LED-DL13WCOB-NW-B
		White	LED-DL13WCOB-NW-W
	5000K 890lm	White	LED-DL13WCOB-5K-W
	5700K 880Im	White	LED-DL13WCOB-CW-W
	6000K 1020lm	Black	LED-DL13WCOB-CW-B





1800 909 306



nedlandsgroup.com.au



sales@nedlandsgroup.com.au



IP20




60° Beam Angle




Certainty at The Speed of Light

PHOTOMETRICS

LED-DL13WCOB | 3000K




LED-DLI3WCOB | 4000K




S DEAM ANGLE (50%):61.4 DEG AVERAGE BEAM ANGLE (50%).61


LED-DL13WCOB | 5000K




LED-DL13WCOB | 5700K



LED-DLI3WCOB | 6000K









nedlandsgroup.com.au



sales@nedlandsgroup.com.au