









LED CANOPY



CL

The POWER-LITE® Canopy lights are suitable for both outdoor and indoor commercial applications such as warehouses, petrol stations and train stations.

APPLICATIONS

Warehouses

Airports

Shopping Centres

Train Stations

Petrol Stations





1800 909 306



nedlandsgroup.com.au




sales@nedlandsgroup.com.au

Certainty at The Speed of Light


(mm) **DIMENSIONS**

CL150W-FM

Cutout 310 x 180



CL75W-SM | CL150W-SM



LED Chip

3030

Lens Type

Mitsubishi PC Lens

Life Expectancy

>54,000 hrs L70

Working Temp

-30°C to +50°C

CRI

>RA70

Power Factor

>0.95

Efficacy

Lumileds Luxeon

LED Driver Meanwell

1-10V Dimming

Up to 130lm/W

Connection

1.5m Power Cable with

connector

Nett Weight

7.45kg

Material

Die Cast Aluminium



IP66

IK08

Beam Angle



Colour

PRODUCT SPECIFICATIONS

LED CANOPY LIGHT



75W









Surface Mount



Replaces 150W-300W MH

Mount Type





CL150W-SM



19,500lm



Replaces



400W-600W MH







Mount Type Flush Mount



CL150W-FM





19,500lm



Replaces 400W-600W MH







1800 909 306



nedlandsgroup.com.au




sales@nedlandsgroup.com.au



PHOTOMETRICS

CL75W | 6500K



CL150W | 6500K

