





## LED CAN

## DOWNLIGHT

## CD25W-NW-W-IP65

The POWER-LITE® LED CAN Downlight is surface mounted, screwless on surface with tempered glass in the front part, which offers a better appearance, high protection level and convenient installation.





1800 909 306 nedlandsgroup.com.au sales@nedlandsgroup.com.au







APPLICATIONS Domestic | Retail Commercial Office



DIMENSIONS Diameter Height

Øl30mm

PHOTOMETRICS

-150

-30

-120

-90

-60

-/+180

600 1200

1800

2400

3000

150

30

0 AVERAGE BEAM ANGLE (50%):57.4 DEG 2135/315,57.6deg

120

90

UNIT:cd

- C0/180,57.4deg - C90/270,57.5deg

C45/225,57.1deg



(mm)

. 130

> LED Chip COB 2835 SMD

50,000 hrs TM-21

Life Expectancy E

SCDM I <6 Macadam steps

Working Temp -20°C to +40°C

Power Factor

**CRI** 80



UGR

**LED Driver** Built-In Dimmable

Mount Type Surface Mount

Carton Qty 12



IP IP65

⊃) 60° Beam Angle

PRODUCT

LED CAN DOWNLIGHT





1800 909 306 nedlandsgroup.com.au sales@nedlandsgroup.com.au

CD25W-NW-W-IP65