



8W LED WIFI INTEGRAL

DOWNLIGHT

ID8W-WF

The POWER-LITE® LED WIFI Integral Downlight saves energy and costs as compared to standard halogen downlights. These come with a built-in WIFI receiver for remote control via Smart Life app. This downlight includes the elimination of UV therefore insects will not be attracted to this light.

Key Features:

- Compatible with Amazon Alexa &
 Google Assistant
- WIFI control, allowing remote control, no distance limits like Bluetooth
- Supply power and WIFI then the app does the rest. This makes it really easy to change over existing downlights
- No WIFI gateway required. App connects
 direct to the light via internet modem
- Everything controlled via mobile but
 still compatible with a standard wall switch

- Family Management from any device
 to dim and change colour temperature
 per room
- Complete Zonal adjustment 5 or more at a time, even one downlight at a time
- Master option to turn everything off at once
- Add as many mobile devices as you like
- You can even set valid time periods for automation to day or night
- Dimming the luminaire can only be achieved
 via the app, not by standard wall dimmer
- NEDLANDS GROUP



1800 909 306



nedlandsgroup.com.au



sales@nedlandsgroup.com.au










APPLICATIONS

Domestic | Retail

Commercial



Certainty at The Speed of Light



Notes:

- Compatible with Clipsal C-Bus dimming systems
- IC-F / IC-4 rated downlights, can be covered and abutted with building materials which can be safely exposed to temperatures of up to 45°

DIMENSIONS	(mm)	
Cutout	90-95	
Diameter	115	
Height	61	

DOWNLIGHT

LED Chip Epistar 2835	Efficacy Up to 911m/W
Life Expectancy 40,000 hrs TM-21	LED Driver Dimmable Integral
Working Temp -20°C to +45°C	IC-4
	Connection
CRI	1.2m Lead & Plug
>80	O service of Observ
	Carton Qty

30

PRODUCT	DESCRIPTION	CODE
8W LED WIFI INTEGRAL	3-CCT, White	ID8W-WF

ACCESSORIES	OPTIONS		CODE
DOWNLIGHT RING	0	Black	ID-BLACK
		Brushed Chrome Finish (304 Marine Grade Stainless Steel)	ID-BC

















5700K







IP54




Beam Angle




Certainty at The Speed of Light

PHOTOMETRICS


ID8W-WF | 3000K



ID8W-WF | 4000K




ID8W-WF | 5700K















sales@nedlandsgroup.com.au