



PUSH / ROTARY SWITCH

DS-RP

Our POWER-LITE® Dimmers are compatible with any POWER-LITE® dimmable products, excluding DALI drivers.

Face plate and switch not included. Fits HPM & Clipsal Wall Plates.





1800 909 306 nedlandsgroup.com.au sales@nedlandsgroup.com.au







APPLICATIONS Residential Commercial



Notes:

* Due to the vast range of LED luminaires currently on the market, POWER-LITE is unable to take liability or responsibility for any incompatibility or warranty issues arising from the use of POWER-LITE dimmers with non-POWER-LITE products.

Control Method One or Two way

Working Temp -20°C to +80°C

Humidity <75%

Compatible Loads POWER-LITE LED Luminaires*

LED Indicator Light Blue Approvals AS/NZS 3100 AS/NZS 3133 IEC 60669-2-1

Dimming Operation Trailing edge

Dimming Type Push button

Over Temp Protection Manual rest

Dimming Range 3% to 100% (Load dependent) Dimmable LED Lamps (dimmer push switch function disabled) 5-250W (Load Min / Max)

Dimmable LED Lamps (dimmer push switch function enabled) 16-250W (Load Min / Max)

Incandescent Halogen (dimmer push switch function disabled) 10-400W (Load Min / Max)

Incandescent Halogen (dimmer push switch function enabled) 16-400W (Load Min / Max)

Carton Qty 20

PRODUCT

PUSH / ROTARY SWITCH DIMMER

CODE

DS-RP





1800 909 306 nedlandsgroup.com.au sales@nedlandsgroup.com.au