









## LED SMD COMMERICAL

# **DOWNLIGHT**

D20-25W-CC

These high efficiency LED SMD POWER-LITE® Downlights are designed for medium to high ceiling installations in retail and public spaces. This Downlight is wattage switchable between 20W and 25W, as well as tri-colour.

APPLICATIONS


Domestic | Retail

Commercial

Healthcare









nedlandsgroup.com.au



sales@nedlandsgroup.com.au

Certainty at The Speed of Light


**DIMENSIONS** 


(mm)


D20-25W-CC

Cutout

230-260







Life Expectancy

50,000 hrs TM-21

**Working Temp** 

-20°C to +45°C

**Power Factor** 

>0.9

CRI

>80

Efficacy

Up to 118lm/W

**LED Driver** 

Triac Dimmable Flicker Free

Connection

LED driver, lead & plug

**Carton Qty** 

20W 25W



3000K






5700K



AC200-240V



White Frame Colour









Beam Angle





1800 909 306



nedlandsgroup.com.au




sales@nedlandsgroup.com.au

Certainty at The Speed of Light

### D20-25W-CC | 3000k

### -150 150 120 -120 -90 UNIT:cd C0/180,100.4 C90/270,100.3 O AVERAGE BEAM ANGLE (50%):100.4 DEG

#### D20-25W-CC I 4000k



### D20-25W-CC | 5700k

