



POWER-LITE®

Certainty at The Speed of Light



LED BACKLIT

PANEL

BLP

The POWER-LITE® LED Backlit Panel is produced using state of the art automated production lines, to provide a cost effective LED panel for all applications.



APPLICATIONS

Office | Retail
Commercial
Healthcare
Domestic
Commercial



☎ 1800 909 306
🌐 nedlandsgroup.com.au
✉ sales@nedlandsgroup.com.au




POWER-LITE®


Certainty at The Speed of Light

DIMENSIONS


BLP16W-30/60-CC



BLP36W-60SQ-CC



BLP36W-120/30-CC



Notes:

- IC Rating for panel only (driver is NOT IC-4 rated)

LED Chip
CRI180 SMD

UGR
<18

Life Expectancy
50,000 hrs TM-21

Efficacy
Up to 116lm/W

SCDM
<6 Macadam steps

LED Driver
Flicker Free

Working Temp
-20°C to +65°C

Replaces
36W replaces 72W

Power Factor
>0.9

Carton Qty
6

CRI
>80



3CCT



White Frame
Colour

PRODUCT SPECIFICATIONS CODE

LED BACKLIT PANEL

16W

300mm x 600mm

IP54

Net Weight 1.56kg

Dimmable Option **Yes**

Connection 1.5m power cable with SAA plug

3000K 1648lm

4000K 1779lm

5700K 1663lm

BLP16W-30/60-CC

36W

600mm x 600mm

IP54

Net Weight 1.56kg

Dimmable Option **Yes**

Connection 1.5m power cable with SAA plug

3000K 3581lm

4000K 3873lm

5700K 3671lm

BLP36W-60SQ-CC

36W

1200mm x 300mm

IP54

Net Weight 1.72kg

Dimmable Option **Yes**

Connection 1.5m power cable with SAA plug

3000K 3506lm

4000K 3887lm

5700K 3575lm

BLP36W-120/30-CC



AC200-240V



120°
Beam Angle



POWER-LITE®

Certainty at The Speed of Light

ACCESSORIES

CODE

FLUSH MOUNT PANEL KIT



To fit Panel Size



300mm x 600mm

Overall Frame Coverage



320mm x 620mm



302mm x 602mm

LED-LPFM-30/60



595mm x 595mm



626mm x 626mm



602mm x 602mm

LED-LPFM-60SQ



1195mm x 295mm



1226mm x 326mm



1202mm x 302mm

LED-LPFM-120/30

CABLE SUSPENSION KIT



Length 1m



Carton Qty 1

LED-LPCSK

LED DRIVERS

Options



DIMMABLE



For 16W LED light panels

BLP16W-D-DIM



DALI DIMMABLE



For 36W LED light panels

BLP36W-D-DIM



For 36W LED light panels

BLP36W-DALI



EMERGENCY KIT



For all LED light panels

LPE-EP

SINGLE PLUG BASE



250V



10A Amp



4 terminals for 2.5mm cable maximum

PBS-413-E



SENSORS

Mount Type

Detection Range

Detection Distance



Recessed



360°



12m

MS-12M-360



360°



16m

MS-8M-360-MW



Surface Mount



360°



6m

MS-6M-360



360°



12m

MS-12M-360-SM



180°



12m

MS-12M-180



360°



16m

MS-8M-360-SM-MW




POWER-LITE®


Certainty at The Speed of Light

PHOTOMETRICS


BLP16W-30/60 | 3000K




BLP16W-30/60 | 4000K




BLP16W-30/60 | 5700K




BLP36W-60SQ | 3000K



BLP36W-60SQ | 4000K



BLP36W-60SQ | 5700K






POWER-LITE®


Certainty at The Speed of Light

PHOTOMETRICS

BLP36W-120/30 | 3000K



BLP36W-120/30 | 4000K



BLP36W-120/30 | 5700K

